

# ACCENT C4 -MODEL: ELC403

Linear Luminaires

# WAC

PROJECT :

TYPE :


## Product Image



## Line Drawing



253MM



## Product Description

The Accent series lighting fixtures use high light efficiency and long lifespan light sources, with an evenly spaced layout design to ensure uniform light output and no shadows. Accent linear lighting fixtures meet the requirements of LED outdoor lighting power consumption design, and their clean and lightweight appearance ensures easy assembly to the exterior wall. Accent lighting fixtures are equipped with flexible cables, allowing for free selection of side or bottom outlets to meet project requirements. The lighting fixtures support DMX512 dimming control with automatic addressing function; The protection level of IP66 for the entire lamp can be widely used in various building lighting, etc.

## Product Features

- Body Material: Aluminum extruded lamp body, aluminum die cast end cover
- Optical System: /
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: Rotating bracket, adjustment range  $\pm 90^\circ$
- Certification: CQC
- IP Rating: IP66
- Insulation Level: Class III
- Operating Temperature:  $-20^\circ\text{C}\sim 50^\circ\text{C}$

## Product Specifications

- LED Type: SMD
- LED Power: 2.4W (Max) /253mm
- Source Lm: 2700K 336LM; 3000K 336 LM; 4000k 360 LM
- LED Lifetime:  $>50000\text{h-L70 /B10-Ta}25^\circ\text{C(LM-80/TM-21)}$
- CCT/CRI: 2700K, Ra80/ 3000K, Ra80/ 4000K, Ra80 / RGB /RGBW
- SDCM: 3 SDCM ( MONO )
- Input: 24V/DC
- Dimming: ON-OFF / DMX512
- Net Weight: 0.6Kg without packing

## Order Model

Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller	CCT	Finish
<b>ELC403-03</b>	253	3(Max)	12	190	ET ON-OFF 24V/DC Power Supply	A 120°	0 W/O Phase	27 2700K 30 3000K 40 4000K	<b>BK</b> Black

Example : ELC403-03ET-A027BK

WAC Lighting  
www.wacighting.com (US)  
www.wacighting.com.cn (China)

Headquarters  
44 Harbor Park Drive • Port Washington, NY  
Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)  
14,Lane 299, Bi Sheng Road, Shanghai 201204,China  
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

WAC Lighting reserves the right to periodically design and update products.2024-01-24

# ACCENT C4 -MODEL: ELC403

Linear Luminaires











PROJECT :

TYPE :


Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller	CCT	Finish
<b>ELC403-03</b>	253	3(Max)	12	190	MT DMX512 Dimming 24V/DC Power Supply	A 120°	<b>1</b> 1 Phase <b>4</b> 4 Phase <b>8</b> 8 Phase	<b>27</b> 2700K <b>30</b> 3000K <b>40</b> 4000K <b>FC</b> RGB <b>FW</b> RGBW	<b>BK</b> Black

Example : ELC403-03MT-A127BK

## Accessories

Item	Description	Pic	Mounting	Quantity Suggested
<b>ELC3-PC-CT002F</b>	Female power connector			1 pc per 8m
<b>ELC3-PC-CT002M</b>	Male power connector			1 pc per 8m
<b>ELC3-SC-CT002F</b>	Female signal connector			1 pc per 32m
<b>ELC3-SC-CT002M</b>	Male signal connector			1 pc per 32m

## LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



<b>MODEL :</b>	ELC403-03MT-A130BK
<b>BEAM ANGLE :</b>	120 °
<b>POWER :</b>	3W/253mm
<b>LUMENS :</b>	190lm
<b>CBCP :</b>	/
<b>EFFICACY :</b>	63lm/W

# ACCENT C4 -MODEL: ELC405

Linear Luminaires

# WAC

PROJECT :

TYPE :

## Product Image



## Line Drawing



## Product Description

The Accent series lighting fixtures use high light efficiency and long lifespan light sources, with an evenly spaced layout design to ensure uniform light output and no shadows. Accent linear lighting fixtures meet the requirements of LED outdoor lighting power consumption design, and their clean and lightweight appearance ensures easy assembly to the exterior wall. Accent lighting fixtures are equipped with flexible cables, allowing for free selection of side or bottom outlets to meet project requirements. The lighting fixtures support DMX512 dimming control with automatic addressing function; The protection level of IP66 for the entire lamp can be widely used in various building lighting, etc.

## Product Features

- Body Material: Aluminum extruded lamp body, aluminum die cast end cover
- Optical System: /
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: Rotating bracket, adjustment range  $\pm 90^\circ$
- Certification: CQC
- IP Rating: IP66
- Insulation Level: Class III
- Operating Temperature:  $-20^\circ\text{C}\sim 50^\circ\text{C}$

## Product Specifications

- LED Type: SMD
- LED Power: 4.8W (Max) /502mm
- Source Lm: 2700K 672LM ; 3000K 672LM ; 4000k 720LM
- LED Lifetime:  $>50000\text{h-L70 /B10-Ta}25^\circ\text{C(LM-80/TM-21)}$
- CCT/CRI: 2700K , Ra80/ 3000K , Ra80 / 4000K , Ra80 / RGB /RGBW
- SDCM: 3 SDCM ( MONO )
- Input: 24V/DC
- Dimming: ON-OFF / DMX512
- Net Weight: 1.0Kg without packing

## Order Model

Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller	CCT	Finish
<b>ELC405-06</b>	502	6(Max)	24	365	ET ON-OFF 24V/DC Power Supply	A 120°	0 W/O Phase	27 2700K 30 3000K 40 4000K	BK Black

Example : ELC405-06ET-A027BK

# ACCENT C4 -MODEL: ELC405

Linear Luminaires











PROJECT :

TYPE :


Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller	CCT	Finish
<b>ELC405-06</b>	502	6(Max)	24	365	MT DMX512 Dimming 24V/DC Power Supply	A 120°	1 1 Phase 4 4 Phase 8 8 Phase	27 2700K 30 3000K 40 4000K FC RGB FW RGBW	<b>BK</b> Black

Example : ELC405-06MT-A127BK

## Accessories

Item	Description	Pic	Mounting	Quantity Suggested
<b>ELC3-PC-CT002F</b>	Female power connector			1 pc per 8m
<b>ELC3-PC-CT002M</b>	Male power connector			1 pc per 8m
<b>ELC3-SC-CT002F</b>	Female signal connector			1 pc per 32m
<b>ELC3-SC-CT002M</b>	Male signal connector			1 pc per 32m

## LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



<b>MODEL :</b>	ELC405-06MT-A130BK
<b>BEAM ANGLE :</b>	120 °
<b>POWER :</b>	6W/502mm
<b>LUMENS :</b>	365lm
<b>CBCP :</b>	/
<b>EFFICACY :</b>	60.8lm/W

# ACCENT C4 -MODEL: ELC410

Linear Luminaires

# WAC

PROJECT :

TYPE :

## Product Image



## Line Drawing



## Product Description

The Accent series lighting fixtures use high light efficiency and long lifespan light sources, with an evenly spaced layout design to ensure uniform light output and no shadows. Accent linear lighting fixtures meet the requirements of LED outdoor lighting power consumption design, and their clean and lightweight appearance ensures easy assembly to the exterior wall. Accent lighting fixtures are equipped with flexible cables, allowing for free selection of side or bottom outlets to meet project requirements. The lighting fixtures support DMX512 dimming control with automatic addressing function; The protection level of IP66 for the entire lamp can be widely used in various building lighting, etc.

## Product Features

- Body Material: Aluminum extruded lamp body, aluminum die cast end cover
- Optical System: /
- Finish: Static electricity powder coating
- Adjustable Angle: /
- Accessories: Rotating bracket, adjustment range  $\pm 90^\circ$
- Certification: CQC
- IP Rating: IP66
- Insulation Level: Class III
- Operating Temperature:  $-20^\circ\text{C}\sim 50^\circ\text{C}$

## Product Specifications

- LED Type: SMD
- LED Power: 9.6W (Max) /1000mm
- Source Lm: 2700K 1344LM ;3000K 1344LM ;4000k 1440LM
- LED Lifetime:  $>50000\text{h-L70 /B10-Ta}25^\circ\text{C(LM-80/TM-21)}$
- CCT/CRI: 2700K , Ra80/ 3000K , Ra80 / 4000K , Ra80 / RGB /RGBW
- SDCM: 3 SDCM ( MONO )
- Input: 24V/DC
- Dimming: ON-OFF/ DMX512
- Net Weight: 1.8Kg without packing

## Order Model

Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller	CCT	Finish
<b>ELC410-12</b>	1000	12(Max)	48	721	ET ON-OFF 24V/DC Power Supply	A 120°	0 W/O Phase	27 2700K 30 3000K 40 4000K	<b>BK</b> Black

Example : ELC410-12ET-A027BK

WAC Lighting  
www.waclighting.com (US)  
www.waclighting.com.cn (China)

Headquarters  
44 Harbor Park Drive • Port Washington, NY  
Phone (516) 515.5000 • Fax (516) 515.5050

WAC Lighting(Shanghai)  
14,Lane 299, Bi Sheng Road, Shanghai 201204,China  
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

WAC Lighting reserves the right to periodically design and update products.2024-01-24

# ACCENT C4 -MODEL: ELC410

Linear Luminaires











PROJECT :

TYPE :


Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller	CCT	Finish
<b>ELC410-12</b>	1000	12(Max)	48	721	MT DMX512 Dimming 24V/DC Power Supply	A 120°	1 1 Phase 4 4 Phase 8 8 Phase	27 2700K 30 3000K 40 4000K FC RGB FW RGBW	<b>BK</b> Black

Example : ELC410-12MT-A127BK

## Accessories

Item	Description	Pic	Mounting	Quantity Suggested
<b>ELC3-PC-CT002F</b>	Female power connector			1 pc per 8m
<b>ELC3-PC-CT002M</b>	Male power connector			1 pc per 8m
<b>ELC3-SC-CT002F</b>	Female signal connector			1 pc per 32m
<b>ELC3-SC-CT002M</b>	Male signal connector			1 pc per 32m

## LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



<b>MODEL :</b>	ELC410-12MT-A130BK
<b>BEAM ANGLE :</b>	120 °
<b>POWER :</b>	12W/1000mm
<b>LUMENS :</b>	721lm
<b>CBCP :</b>	/
<b>EFFICACY :</b>	60lm/W