

# FUEGO PRO- MODEL: EIL2

In-ground Luminaires

# WAC LIGHTING

Responsible Lighting®


PROJECT:

TYPE:

## Product Image



## Line Drawing



## Product Description

The Fuego Pro series buried lights are perfectly embedded and installed, with good consistency in light output, surface light output, and no visible light source particle sensation. The lamps are suitable for residential areas, hotels, squares, parks, and courtyards, and are suitable for local and decorative lighting.

## Product Features

- Body Material: Aluminum extruded lamp body, aluminum die cast end cover
- Optical System: Milky white optical glass
- Finish: electrostatic powder coating
- Adjustable Angle:
- Accessories: Including embedded parts
- Certification: CQC
- IP Rating: IP67
- Insulation Level: Class III
- Operating Temperature: -20°C~50°C

## Product Specifications

- LED Type: SMD
- Light source power: 11W (Max)
- Source Lm: 2700K 1100lm; 3000K 1200lm; 4000K 1300lm
- LED Lifetime: >50000h-L70 / B10-Ta25°C(LM-80 / TM-21)
- CCT/CRI: 2700K, Ra80 / 3000K, Ra80 / 4000K, Ra80 / RGB
- SDCM: 3 SDCM
- Input: 24V DC
- Dimming: ON-OFF or DMX512 dimming control
- Net Weight: Approximately 2.8kg, without packaging

## Order Model

Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller (m)	CCT	Finish
EIL210-12	1006	11(Max)	120	764	ET ON-OFF 24V DC Power Supply	F Frosted	0 W/O Phase	27 2700K	BK Black GY Gray
EIL205-06	513	6(Max)	60	357				30 3000K	
								40 4000K	

Example: EIL210-12ET-F027BK

## WAC Lighting

www.waclighting.com (US)  
www.waclighting.com.cn (China)

## Headquarters

44 Harbor Park Drive • Port Washington,  
NY Phone (516) 515.5000 • Fax (516)

## WAC Lighting Technology (Shanghai) Co., Ltd

14, Lane 299, Bi Sheng Road, Shanghai 201204  
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

# FUEGO PRO- MODEL: EIL2

In-ground Luminaires

# WAC LIGHTING

Responsible Lighting®

PROJECT:

TYPE:

Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller (m)	CCT	Finish
<b>EIL210-12</b>	1006	11(Max)	120	764	MT DMX512 Dimming 24V DC Power Supply	F Frosted	1 1 Phase 4 4 Phase	27 2700K 30 3000K 40 4000K FC RGB	BK Black GY Gray
<b>EIL205-06</b>	513	6(Max)	60	357					

Example: EIL210-12MT-F127BK

## accessory

Item	Description	Pic	Mounting
<b>EIL2-RC059-BK</b>	Recessed casing 513mm BK		
<b>EIL2-RC059-GY</b>	Recessed casing 513mm GY		
<b>EIL2-RC100-BK</b>	Recessed casing 1006mm BK		
<b>EIL2-RC100-GY</b>	Recessed casing 1006mm GY		
<b>EIL2-PC-CT002F</b>	ET Female connector		
<b>EIL2-PC-CT002M</b>	ET Male connector		
<b>ELC3-SC-CT002F</b>	MT Female connector		
<b>ELC3-SC-CT002M</b>	MT Male connector		

WAC Lighting  
www.waclighting.com (US)  
www.waclighting.com.cn (China)

Headquarters  
44 Harbor Park Drive • Port Washington,  
NY Phone (516) 515.5000 • Fax (516)

WAC Lighting Technology (Shanghai) Co., Ltd  
14, Lane 299, Bi Sheng Road, Shanghai 201204  
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598

# FUEGO PRO- MODEL: EIL2

In-ground Luminaires


# WAC LIGHTING

Responsible Lighting®


PROJECT:

TYPE:

## LIGHT DISTRIBUTION@3000K LUMINAIRE DATA



<b>MODEL:</b>	EIL210-12ET-F027BK
<b>BEAM ANGLE:</b>	115°
<b>POWER:</b>	13.4W
<b>LUMENS:</b>	763.6 lm
<b>CBCP:</b>	/
<b>EFFICACY:</b>	56.8 lm /W



<b>MODEL:</b>	EIL205-06ET-F027BK
<b>BEAM ANGLE:</b>	115°
<b>POWER:</b>	6.8W
<b>LUMENS:</b>	357 lm
<b>CBCP:</b>	/
<b>EFFICACY:</b>	52.5 lm /W