# INVISILED PIXELS - MODEL: LED-P

Linear Luminaires

## PROJECT:

## **Product Image**

u o osu, oso	e e	010,010	e e	UIL, UIL
o o o to ju to	0,p	u su <sup>i</sup> ju su	U.L.D	u≣u <sup>4</sup> ju≣u
o"'o o 10, o 10	U U		e <sup>rri</sup> e	010,010
e e e e e e e e e e e e e e e e e e e	00	u su <sup>d k</sup> u su	Unit	UIU <sup>3 S</sup> UIU
o"b olo, plo	00	010,010	DUD	U EU, ju EU
unp orothore	0,0	010401010	e <sub>tt</sub> e	o ∎e <sup>a</sup> j <sup>e</sup> e ∎e
ollo oto la la	00	010,010	e e	e i e <sub>e e</sub> e i e
000 010,010		· E E-		-6 6-
omb ofo <sub>1</sub> pfo	e <sub>m</sub> p	UIU <sup>1</sup> UIU	Dark	o in the in

010	o''''b	0 20	010	o''''b	0 20.	000	000	010	010	o''''b	0
'n≣o	o <u></u> p	010	010	op	010	o z o	o <u></u> p	oto	0 g o	o <u></u> p	0
0 2 0	o'''b	0 80.	010	o'''b	0 20.	0 2 0	00	0 20.	0 20	o‴b	0
'n≣o	0,0	ogo	010	op	o≣o	°o≣o	PP	oto	σΞσ	op	0
010	o'''b	0 80.	010	o''''b	0 20.	010	o''''o	o # 0.	010	o''''o	Ø
010	op	0 20	010	9P	0 20	020	PP	0 20	020	9p	0
010	o''''o	0 20.	010	o''''b	0 \$ 0.	0 20	o‴``o	0 80.	D E O	o''''o	a
010	op	0 20	010	op	0 20	020	op	0 10	010	op	0
DED	00	0 20.	010	0 0	0 10.	0 20	o'''b	o E O	010	o‴`o	0
010	op	oto	010	0	o to	010	op	o to	010	op	٥
010	o'''b	0 20.	010	o''''b	0 20.	010	o''''o	0 20.	.o≣o	o''''b	0
010	Q., p	0 20	0 20	Q., p	010	010	Q.,.P	010	010	Q.,.P	O

#### **Product Description**

InvisiLED Pixels RGB is designed for luminous ceiling and luminous wall, easy to install, can be cut along the design grid to make creative modeling. Suitable for hotel villas, commercial space and other places.

#### **Product Features**

Body Material: Flexible copper FPCB

• IP Rating:

• Operating Temperature: board IP20 -20°C~50°C

## **Product Specifications**

• LED:	SMD
• Lamp power:	60W/pcs(R/G/B single point 20W each)
• Size:	240mm*480mm
• Source Lm:	>36000h-L70 / B10-Ta25°C (LM-80/TM-21)
• CCT:	RGB
• Input:	24V
• Dimming;	Full page control, support 0-10V, DMX512,
	DALI and other dimming control modules
• Net Weight:	0.3Kg without packing

### **Order Model**

Model	LED	Size	Series
LED-P InvisiLED Pixels	<b>60</b> 60W/pcs	<b>2448</b> 240mm*480mm	FC RGB

Example: LED-P60-2448-FCG



TYPE:

## Line Drawing