

SPECIFICATIONS  
**BEACON X3 ACCENT C3**  
MODEL: ELC310



**WAC LIGHTING**  
Responsible Lighting®

PROJECT:

LUMINAIRE CODE:

Product image

Line drawing



**Product description**

Beacon X3 series luminaires are designed with equal spacing of light sources with high light efficiency and long life, which ensures uniform lighting effect and no shadows. Linear luminaires meet the requirements of LED outdoor lighting power design. The slender luminaires body and neat appearance ensure easy install to the outer wall. Beacon luminaires are wired from the bottom of the luminaires and are flexible to meet the project requirements of the power cable. IP66 waterproof grade. DV24V ensures effective transmission of feeder and signal, and low line loss. DMX512 dimming control with automatic programming function.

**Structure features**

- **Body material:** Aluminum alloy extrusion body, Die-casting end cap
- **Optical system:** /
- **Surface treatment:** Electrostatic powder spraying
- **Adjustable direction:** /
- **Accessories:** Stainless steel fixing bracket
- **Certification:** CQC
- **IP grade:** IP66
- **Class of insulation:** Class III
- **Environmental temperature:** -20°C~50°C

**Product specifications**

- **Light source:** SMD
- **Light power:** 9.6W ( Max ) /1000mm
- **Lumens:** 2700K 1344lm ; 3000K 1344lm ; 4000k 1440lm
- **Light source life:** >50000h-L70/B10-Ta25°C (LM-80/TM-21)
- **CCT/CRI:** 2700K,Ra80/3000K,Ra80/4000K,Ra80/RGB/RGBW
- **SDCM:** 3 SDCM
- **Input:** 24V/DC
- **Dimming control:** ON-OFF or DMX512
- **Weight:** About 1.8Kg,No packaging

**Order number**

Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller (m)	CCT	Finish
ELC310-12	1000	12(Max)	48	721	ET ON-OFF 24V/DC Power Supply	A 120°	0 W/O Phase	27 2700K 30 3000K 40 4000K	BK Black

Example: ELC310-12ET-A027BK

**Headquarters**

44 Harbor Park Drive, Port Washington, NY  
Phone (516) 515.5000 • Fax (516) 515.5050  
www.waclighting.com

**WAC Lighting (Shanghai)**

14 Lane 299, Bi Sheng Road Shanghai 201204  
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598  
www.waclighting.com.cn

**WAC Lighting - International sales**

Room 3207-3208, Building 4,Tian An Cloud Park,  
ShenZhen, Guangdong 518129  
www.waclighting.io

SPECIFICATIONS  
**BEACON X3 ACCENT C3**  
 MODEL: ELC310

**WAC LIGHTING**  
 Responsible Lighting®

PROJECT:


LUMINAIRE CODE:

Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller (m)	CCT	Finish
ELC310-12	1000	12(Max)	48	721	MT DMX512 Dimming 24V/DC Power Supply	A 120°	1 1 Phase 4 4 Phase 8 8 Phase	27 2700K 30 3000K 40 4000K FC RGB FW RGBW	BK Black

Example: **ELC310-12MT-A127BK**

**Accessories**

**Photometry@3000K DATA**



**Model:** ELC310-12MT-A130BK

**Beam:** 120°

**Power:** 12W/1000mm

**Lumens:** 721lm

**CBCP:** /

**Efficacy:** 60lm/W

**Headquarters**

44 Harbor Park Drive, Port Washington, NY  
 Phone (516) 515.5000 • Fax (516) 515.5050  
[www.waclighting.com](http://www.waclighting.com)

**WAC Lighting (Shanghai)**

14 Lane 299, Bi Sheng Road Shanghai 201204  
 Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598  
[www.waclighting.com.cn](http://www.waclighting.com.cn)

**WAC Lighting - International sales**

Room 3207-3208, Building 4, Tian An Cloud Park,  
 ShenZhen, Guangdong 518129  
[www.waclighting.io](http://www.waclighting.io)