

SPECIFICATIONS
BEACON X3 ACCENT C3
MODEL: ELC305

WAC LIGHTING
Responsible Lighting®



PROJECT:

LUMINAIRE CODE:

Product image



Line drawing



Product description

Beacon X3 series luminaires are designed with equal spacing of light sources with high light efficiency and long life, which ensures uniform lighting effect and no shadows. Linear luminaires meet the requirements of LED outdoor lighting power design. The slender luminaires body and neat appearance ensure easy install to the outer wall. Beacon luminaires are wired from the bottom of the luminaires and are flexible to meet the project requirements of the power cable. IP66 waterproof grade. DV24V ensures effective transmission of feeder and signal, and low line loss. DMX512 dimming control with automatic programming function.

Structure features

- **Body material:** Aluminum alloy extrusion body, Die-casting end cap
- **Optical system:** /
- **Surface treatment:** Electrostatic powder spraying
- **Adjustable direction:** /
- **Accessories:** Stainless steel fixing bracket
- **Certification:** CQC
- **IP grade:** IP66
- **Class of insulation:** Class III
- **Environmental temperature:** -20°C~50°C

Product specifications

- **Light source:** SMD
- **Light power:** 4.8W (Max) /502mm
- **Lumens:** 2700K 672lm ; 3000K 672lm ; 4000k 720lm
- **Light source life:** >50000h-L70/B10-Ta25°C (LM-80/TM-21)
- **CCT/CRI:** 2700K,Ra80/3000K,Ra80/4000K,Ra80/RGB/RGBW
- **SDCM:** 3SDCM
- **Input:** 24V/DC
- **Dimming control:** ON-OFF or DMX512
- **Weight:** About 1Kg,No packaging

Order number

Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller (m)	CCT	Finish
ELC305-06	502	6(Max)	24	365	ET ON-OFF 24V/DC Power Supply	A 120°	0 W/O Phase	27 2700K 30 3000K 40 4000K	BK Black

Example: **ELC305-06ET-A027B**

Headquarters

44 Harbor Park Drive, Port Washington, NY
Phone (516) 515.5000 • Fax (516) 515.5050
www.waclighting.com

WAC Lighting (Shanghai)

14 Lane 299, Bi Sheng Road Shanghai 201204
Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598
www.waclighting.com.cn

WAC Lighting - International sales

Room 3207-3208, Building 4,Tian An Cloud Park,
ShenZhen, Guangdong 518129
www.waclighting.io

SPECIFICATIONS
BEACON X3 ACCENT C3
 MODEL: ELC305

WAC LIGHTING
 Responsible Lighting®

PROJECT:


LUMINAIRE CODE:

Model	Length (mm)	Power (W)	LEDs (quantity)	Max Lumens (lm)	Control Systems	Beam	Phase Controller (m)	CCT	Finish
ELC305-06	502	6(Max)	24	365	MT DMX512 Dimming 24V/DC Power Supply	A 120°	1 1 Phase 4 4 Phase 8 8 Phase	27 2700K 30 3000K 40 4000K FC RGB FW RGBW	BK Black

Example: **ELC305-06MT-A127BK**

Accessories

Photometry@3000K DATA



Model:	ELC305-06MT-A130BK
Beam:	120°
Power:	6W/502mm
Lumens:	365lm
CBCP:	/
Efficacy:	60.8lm/W

Headquarters

44 Harbor Park Drive, Port Washington, NY
 Phone (516) 515.5000 • Fax (516) 515.5050
 www.waclighting.com

WAC Lighting (Shanghai)

14 Lane 299, Bi Sheng Road Shanghai 201204
 Phone (86.21) 3393.3558 • Fax (86.21) 3362.1598
 www.waclighting.com.cn

WAC Lighting - International sales

Room 3207-3208, Building 4, Tian An Cloud Park,
 ShenZhen, Guangdong 518129
 www.waclighting.io